

Delivering Engineered Packaging Solutions

◆ COMPETITIVE ◆ QUALITY ◆ EXPERIENCED ◆ RELIABLE ◆ INNOVATIVE ◆ INTEGRATED

PL108 LIDDING FILM - *PEELABLE & HIGH BARRIER*

TRANSPARENT PEELABLE & HIGH BARRIER FILM

PL108 Perfect Application

- Peelable on APET, CPET, PP, PS, PVC and etc.
- Perfect for oven cooking of Frozen Entrees, BBQ Meats, Fresh Vegetables.
- Suitable to use in conventional oven
- Available in 216 gauge to 310 gauge.

Solvent Free



PL108 The Ideal Film

- Transparent High Barrier Film
- High Gas-Barrier version available
- Also available in White Opaque & Metalized
- Allows printing in common techniques

Property		Unit	Value					
Total Thickness		gauge	216	256	267	295	302	310
Yield		Sq. m /lb.	12.1	10.6	10.2	9.10	9.0	8.7
Roll Width		In.	3.75 to 47					
Standard Roll Length		Ft	1625, 325					
Roll Outer Diameter		in	8 to 13.75					
Roll Inner Diameter		in	Standard 3" core					
Roll Weight		lbs	11 to 440					
High Barrier			Optional					
Printable			Yes					
Anti-Fog			Optional					
Permeability		$\frac{g}{m^2 \times d}$	Standard		High Barrier			
	H ² O	$\frac{ml}{m^2 \times d \times bar}$	5		4			
	CO ²		450		23			
	O ²		165		8			

¹ Test Conditions 25° C, 50% RH, 1 Bar

PL108 Films, all of the raw material used in the making of the films are approved for food contact in accordance to ECC and/or the FDA regulations.

