

## Delivering Engineered Packaging Solutions

◆ COMPETITIVE ◆ QUALITY ◆ EXPERIENCED ◆ RELIABLE ◆ INNOVATIVE ◆ INTEGRATED

### PL128 LIDDING FILM - *ANTI-FOG & PEELABLE SEAL*

#### TRANSPARENT PEELABLE & ANTI-FOG FILM **Solvent Free**

##### PL128 Perfect Application

- Easy Peel onto Polypropylene (PP) AND Polystyrene (PS) Trays
- Excellent for produce packaging, vegetable spreads such as Hummus, eggplant, cheese spreads and etc.
- Available in 216 gauge to 256 gauge.



##### PL128 The Ideal Film

- Transparent Anti-Fog Film
- High Gas-Barrier version available
- Allows printing in common techniques

Property	Unit	Value		
Total Thickness	gauge	216	256	
Yield	sq. in /lb.	13.0	11.0	
Roll Width	in.	3.75 to 47		
Standard Roll Length	Ft	1625, 3250		
Roll Outer Diameter	in.	8 to 13.75		
Roll Inner Diameter	in.	standard 3" cord		
Roll Weight	lbs	11 to 440		
High Barrier		Optional		
Printable		Yes		
Anti-Fog		Optional		
Permeability		<b>Standard</b>	<b>High Barrier</b>	
	H <sup>2</sup> O	$\frac{\text{gr.}}{\text{m}^2 \times 24 \text{ hrs.}}$	5	4
	CO <sup>2</sup>	$\frac{\text{ml}}{\text{M}^2 \times 24 \text{ hrs.}}$	450	23
	O <sup>2</sup>		165	8

<sup>1</sup> Test Conditions 25° C, 50% RH, 1 Bar

**PL128** Films, all of the raw material used in the making of the films are approved for food contact in accordance to ECC and/or the FDA regulations.

