

Delivering Engineered Packaging Solutions

◆ COMPETITIVE ◆ QUALITY ◆ EXPERIENCED ◆ RELIABLE ◆ INNOVATIVE ◆ INTEGRATED

PL133 LIDDING FILM - LOCK SEAL & HIGH GAS BARRIER

TRANSPARENT LOCK SEAL HIGH BARRIER FILM

PL133 Perfect Application

- Lock Seal onto Polypropylene (PP) Trays
- Excellent for Fresh or Frozen plated entrees.
- All typical for raw meats, poultry and fish where anti-fog is not required.
- Available in 177 gauge to 295 gauge.

Solvent Free



PL133 The Ideal Film

- Transparent Film
- High Gas-Barrier
- Allows for common printing techniques

Property	Unit	Value			
Total Thickness	gauge	177	216	256	295
Yield	sq. in /lb.	14.79	12.1	10.57	9.09
Roll Width	in.	3.75 to 47			
Standard Roll Length	Ft	1625, 3250			
Roll Outer Diameter	in.	8 to 13.75			
Roll Inner Diameter	in.	standard 3" core			
Roll Weight	lbs	11 to 440			
High Barrier		Optional			
Printable		Yes			
Anti-Fog		Optional			
Permeability		<u>gr</u>	Standard	High Barrier	
	H2O	m ² x 24 hrs.	5	2	
	CO2	<u>ml</u>	450	23	
	O2	m ² x 24 hrs.	165	6	

¹ Test Conditions 25° C, 50% RH, 1 Bar

PL133 Films, all of the raw material used in the making of the films are approved for food contact in accordance to ECC and/or the FDA regulations.

