

Delivering Engineered Packaging Solutions

◆ COMPETITIVE ◆ QUALITY ◆ EXPERIENCED ◆ RELIABLE ◆ INNOVATIVE ◆ INTEGRATED

PL140 LIDDING FILM - *HARD PEEL to LOCK & HIGH BARRIER*

TRANSPARENT HARD PEEL & HIGH BARRIER

PL140 Perfect Application

- Specially formulated for PS, provides a hard peel to lock seal depending on machine parameters.
- Excellent for fresh or frozen entrees and where tamper evidence is needed.
- Suitable to use in microwave and conventional oven
- Available in 138 gauge to 295 gauge.

Solvent Free



PL140 The Ideal Film

- Transparent High Barrier Film
- High Gas-Barrier version available
- Also available in White Opaque & Metalized
- Allows printing in common techniques

Property		Unit	Value			
Total Thickness		gauge	137	177	216	295
Yield		Sq. m /lb.	18.6	14.79	12.1	9.09
Roll Width		In.	3.75 to 47			
Standard Roll Length		Ft	1625, 3250			
Roll Outer Diameter		In.	8 to 13.75			
Roll Inner Diameter		In.	Standard 3" core			
Roll Weight		Lbs.	11 to 440			
High Barrier			Optional			
Printable			Yes			
Anti-Fog			Optional			
Permeability			Standard		High Barrier	
	H ₂ O	$\frac{g}{m^2 \times d}$	5		4	
	CO ₂	$\frac{ml}{m^2 \times d \times bar}$	450		23	
	O ₂		165		8	

¹ Test Conditions 25° C, 50% RH, 1 Bar

PL140 Films, all of the raw material used in the making of the films are approved for food contact in accordance to ECC and/or the FDA regulations.

