

Delivering Engineered Packaging Solutions

◆ COMPETITIVE ◆ QUALITY ◆ EXPERIENCED ◆ RELIABLE ◆ INNOVATIVE ◆ INTEGRATED

RLP50 LIDDING FILM - *ANTI-FOG*

ANTI-FOG PRINTABLE FILM

RLP150 The Ideal Film

- Seals through contamination
- Excellent hot-tack
- Peelable Hot or Old
- Printable with corona treatment



RL150 Perfect Application

- Lidding to APET & CPET trays types
- Suitable for cap liner
- Available in varies gauges

Property	Unit	Value			
Total Thickness	mm	0.035	0.045	0.055	0.065
Yield	Sq. m /kg.	27	21.4	17.5	15.3
Roll Width	mm	80 to 1200			
Standard Roll Length	Meter	500, 1000			
Roll Outer Diameter	mm	200 to 350			
Roll Inner Diameter	mm	76 (+ -) 2%			
Roll Weight	kg	5 to 200			
High Barrier		Optional			
Printable		Yes			
Anti-Fog		Optional			
Permeability		$\frac{\text{gr.}}{\text{m}^2 \times 24 \text{ hrs.}}$ $\frac{\text{ml}}{\text{M}^2 \times 24 \text{ hrs.}}$	Standard	High Barrier	
	H ² O		20 - 22	6 - 8	
	CO ²		600 - 700	22 - 23	
	O ²		130 - 150	8 - 10	

¹ Test Conditions 25° C, 50% RH, 1 Bar

RLP50 Films, All of the raw material used in the making of the films are approved for food contact according to the FDA/USDA standards by the material manufacturers

RLP50 Films, comply with the requirements set forth in FDA/USDA regulations 21.CFR, section 177.1520 (Polyethylene), 177.1360 (EVOH), 175.105 (Adhesive), 177.1500 (Polyamide), and 177.1330 (Ionomer), 177.1350, 177.1570 (EP film).

